21998

Serial No...

APPLICATION FOR PERMIT

TO	APPROPRIATE	THE	DUDLIC	WATEDS	ΩE	THE	CTATE	ΩE	NEVADA
10	APPRUPRIATE	INE	LODLIC	AA WIEK?	ŲΓ	100	SIMIE	Ur	IAEAWAW

Date	of filing in State Engineer's Office. MAY 1 5 1964
	rned to applicant for correction.
Map	filed
•	The applicant W.M.K. TRANSIT MIX, INC.,
of	Las Vegas , County of Clark ,
State	of
	s of the State of Nevada, as hereinafter stated. (If applicant is a corporation, give date and place of incorpora-
tion;	if a copartnership or association, give names of members.)
	1954 - Carson City, Nevada
	en transporter i provincia de la compansión de <u>la contrata de la contrata de la contrata de la contrata de la</u> La contrata de la co
	The source of the proposed appropriation is Las Vegas Artesian Basin (Underground source) Name of stream, lake or other source.
-	
2.	The amount of water applied for issecond-feet One second-foot equals 448.83 gals. per min.
7,	(a) If stored in reservoir give number of acre-feetacre-feet
3.	The water to be used for Industrial (gravel plant) and Domestic Use
	If use is for:
	(a) Irrigation (state number of acres to be irrigated)
	(b) Stockwater (state number and kinds of animals to be watered)
	(c) Other use (describe fully under "No. 11. Remarks")
	(d) Power:
	(1) Horsepower developed
	(2) Point of return of water to stream
	The water is to be diverted from its source at the following point: NEZ SEZ Section 21. Township 21.
	South Range 60 East, M.D.B.&M., County of Clark, State of Nevada, or at a point
	Describe as being within a 40-acre subdivision of public survey, and by course and distance to a section corner. If on unsurveyed land, from which the East ½ corner of said Section 21 bears North 06° 50′ 27′ East a
	it should be stated. distance of 1204.00 feet. Place of use NW SW SW NE SW NW SE NW SE Of Section 21, Township 21 South,
0,	Describe by legal subdivision, if on unsurveyed land it should be so stated. Range 60 East, M.D.B.&M., County of Clark, State of Nevada.
	Use will begin about January 1st and end about December 31st , of each year. Month Month
	Description of proposed works. (Under the provisions of NRS 535.010 you may be required to submit plans and
	specifications of your diversion or storage works.) drilled well, 10 inch casing, with mis-
	cellaneous size pipes to points of use. State manner in which water is to be diverted, whether by dam or other works, whether through pipes, ditches, flumes, or other conduits.

	Estimated cost of worl	KS	\$8,000,00
10.	Estimated time require	ed to construct works	60 days
11.	Remarks The	water is to be use	ed for a gravel washing plant
			<u></u>
Apŗ	•	ANSIT MIX, INC.	
	No.		By s/Bennett J. Vasey
Con	nparedawb/ns	hs/ns	Bennett J. Vasey - State Water-Right Surveyorc/o Tyson Engineering Co. Inc.
			
•		APPROVAL	OF STATE ENGINEER
	This is to certify that	I have examined the fore	egoing application, and do hereby grant the same, subject to the
an th pr	d is further s e Las Vegas Va oduce but not	ubject to revoc lley Water Dist to exceed 1.0 c	mit is issued subject to existing rights ation if and when water is available from rict, and is limited to what the well will of.s., and with the understanding that all ponded after use and reused. A meter must
<u>be</u>	installed in	the discharge p	pipe line, near the point of diversion, and
ac	curate measure	ments must be k	ept of water placed to beneficial use. It
is	understood th	at this right m	night allow for a measurable leversing of the
			<u>ust_allow_lor_a_reasonable_lowering_or_the</u>
	•		,
st	atic water leve	el. The well s	hall be equipped with a 2-inch opening and
st an	atic water leve air line for m	el. The well s	hall be equipped with a 2-inch opening and to water. If well is flowing, a valve mu
st an be	atic water leve air line for minstalled and	el. The well s measuring depth maintained to	hall be equipped with a 2-inch opening and to water. If well is flowing, a valve muprevent waste. This source is located wit
an be in	atic water lever air line for many installed and an area design	el. The well s measuring depth maintained to hated by the St	to water. If well is flowing, a valve muprevent waste. This source is located with attemption and the Engineer pursuant to NRS 530.030; then
an be in	atic water lever air line for manual and and area designer, the State manual and and and area designer.	el. The well s measuring depth maintained to nated by the St retains the rig	to water. If well is flowing, a value muprevent waste. This source is located with ate Engineer pursuant to NRS 530.030; then the to regulate the use of the water herein
an be in for	atic water lever air line for many and area designanted at any and anted at any and anted at any and anted at any and anted at any and and and any and and any and	el. The well s measuring depth maintained to nated by the St retains the rig	to water. If well is flowing, a valve mure prevent waste. This source is located with at Engineer pursuant to NRS 530.030; then the to regulate the use of the water herein
an be in for	atic water lever air line for manual and and area designment, the State manted at any area amount of water to be	el. The well s measuring depth maintained to nated by the St retains the rig nd all times. appropriated shall be lim	to water. If well is flowing, a valve must prevent waste. This source is located with ate Engineer bursuant to NRS 530.030; then the to regulate the use of the water herein mited to the amount which can be applied to beneficial use, and
an be in for	atic water lever air line for many and area designment, the State manted at any and amount of water to be so exceed	el. The well s measuring depth maintained to hated by the St retains the rig nd all times. appropriated shall be lim	to water. If well is flowing, a valve must prevent waste. This source is located with attemption and the Engineer pursuant to NRS 530.030; then the to regulate the use of the water herein which can be applied to beneficial use, and cubic feet per second.
an be in for	atic water lever air line for many and area designment, the State manted at any and amount of water to be so exceed	el. The well s measuring depth maintained to hated by the St retains the rig nd all times. appropriated shall be lim	to water. If well is flowing, a valve must prevent waste. This source is located with ate Engineer bursuant to NRS 530.030; then the to regulate the use of the water herein mited to the amount which can be applied to beneficial use, and
an be in for	atic water lever air line for mainstalled and an area designed and an area designed anted at any area amount of water to be so exceed	el. The well s measuring depth maintained to nated by the St retains the rig nd all times. appropriated shall be lim 0	to water. If well is flowing, a valve must prevent waste. This source is located with attemption and the Engineer pursuant to NRS 530.030; then the to regulate the use of the water herein which can be applied to beneficial use, and cubic feet per second.
an be in for	atic water lever air line for mair line for mair line for mair led and an area designer, the State manted at any areamount of water to be so exceed	el. The well s measuring depth maintained to nated by the St retains the rig nd all times. appropriated shall be lim 0 ater per cubic	to water. If well is flowing, a valve must prevent waste. This source is located with ate Engineer pursuant to NRS 530.030; then that to regulate the use of the water herein mitted to the amount which can be applied to beneficial use, and cubic feet per second but not to exceed yard of gravel washed.
an be in for gra The 450	air line for mainstalled and an area designate, the State manted at any area amount of water to be a exceed	el. The well s measuring depth maintained to nated by the St retains the rig nd all times. appropriated shall be lim 0 ater per cubic all begin on or before	to water. If well is flowing, a valve must prevent waste. This source is located with at Engineer pursuant to NRS 530.030; then that to regulate the use of the water herein ited to the amount which can be applied to beneficial use, and cubic feet per second but not to exceed yard of gravel washed. February 21, 1965
an be in for gra Fhe quant t 450 Actu	air line for mainstalled and an area designer, the State manted at any area amount of water to be so exceed	el. The well s measuring depth maintained to nated by the St retains the rig nd all times. appropriated shall be lim 0 ater per cubic work shall be filed before ith reasonable diligence a	to water. If well is flowing, a valve must prevent waste. This source is located with ate Engineer pursuant to NRS 530.030; then the to regulate the use of the water herein mitted to the amount which can be applied to beneficial use, and cubic feet per second but not to exceed yard of gravel washed. February 21, 1965
an be in for gri	atic water lever air line for mainstalled and an area designer, the State manted at any areamount of water to be so exceed	el. The well s measuring depth maintained to nated by the St retains the rig nd all times. appropriated shall be lim 0 ater per cubic all begin on or before work shall be filed before ith reasonable diligence a	to water. If well is flowing, a valve must prevent waste. This source is located with ate Engineer bursuant to NRS 530.030; then that to regulate the use of the water herein nited to the amount which can be applied to beneficial use, and cubic feet per second but not to exceed yard of gravel washed. February 21, 1965 March 21, 1965
an be in for gra The Actu Proce Wor App	air line for mater lever air line for material and an area designment, the State manted at any amount of water to be so exceed	el. The well s measuring depth maintained to hated by the St retains the rig nd all times. appropriated shall be lim 0 ater per cubic sall begin on or before work shall be filed before ith reasonable diligence a shall be filed before.	to water. If well is flowing, a valve must be revent waste. This source is located with ate Engineer bursuant to NRS 530.030; there that to regulate the use of the water herein that to the amount which can be applied to beneficial use, and cubic feet per second to but not to exceed yard of gravel washed. February 21, 1965 March 21, 1966 March 21, 1966 March 21, 1966 March 21, 1966
an be in for The Actu Proce App	atic water lever air line for mair line for the State manual amount of water to be so exceed	el. The well s measuring depth maintained to nated by the St retains the rig nd all times. appropriated shall be lim 0 ater per cubic all begin on or before work shall be filed before ith reasonable diligence a shall be filed before eficial use shall be made of water to beneficial use shall	to water. If well is flowing, a valve must be revent waste. This source is located with ate Engineer pursuant to NRS 530.030; there that to regulate the use of the water hereing that to the amount which can be applied to beneficial use, and cubic feet per second but not to exceed yard of gravel washed. February 21, 1965 March 21, 1966 March 21, 1966 March 21, 1966 March 21, 1967
an be in for The Acturate Process App Process Map Proc	air line for mainstalled and an area designer, the State manted at any areamount of water to be so exceed	measuring depth maintained to nated by the St retains the rig nd all times. appropriated shall be lim o ater per cubic all begin on or before work shall be filed before ith reasonable diligence a shall be filed before eficial use shall be made o vater to beneficial use shall be filed before	thall be equipped with a 2-inch opening and to water. If well is flowing, a valve must be prevent waste. This source is located with ate Engineer bursuant to NRS 530.030; then the to regulate the use of the water herein which to the amount which can be applied to beneficial use, and cubic feet per second , but not to exceed ward of gravel washed. February 21, 1965 March 21, 1966 March 21, 1966 March 21, 1967 March 21, 1967 March 21, 1967 March 21, 1967
an be in for the desired work work work work work work work with the desired work work work work work work work work	atic water lever air line for minstalled and an area designer, the State manted at any an amount of water to be so exceed. 1.00 gallons of water to be sall construction work should be prosecuted with the formulation of water to be set of of the application of work should be support of proof of the mencement of work filed.	measuring depth maintained to nated by the St retains the rig nd all times. appropriated shall be lim o ater per cubic all begin on or before work shall be filed before ith reasonable diligence a shall be filed before eficial use shall be made o vater to beneficial use shall be filed	mited to the amount which can be applied to beneficial use, and cubic feet per second but not to exceed yard of gravel washed. February 21, 1965 March 21, 1966 March 21, 1966 March 21, 1967
an be in for grid and the state of the state	atic water lever air line for minstalled and an area designer, the State manted at any areamount of water to be so exceed	measuring depth maintained to nated by the St retains the rig nd all times. appropriated shall be lim o ater per cubic all begin on or before work shall be filed before ith reasonable diligence a shall be filed before eficial use shall be made o vater to beneficial use shall be filed before contains the rig nd all times.	to water. If well is flowing, a valve must be prevent waste. This source is located with ate Engineer bursuant to NRS 530.030; there that to regulate the use of the water herein which can be applied to beneficial use, and cubic feet per second , but not to exceed yard of gravel washed. February 21, 1965 March 21, 1965 March 21, 1966 March 21, 1966 March 21, 1967 March 21, 1967